# CRYSTAL ICE



## Optional Accessories

- Water filter
  - Inhibits harmful bacteria growth
  - Eliminates harmful substance / particles up to 0.5µm



### Optional Accessories for CTM-series & CTF-series

- lce bin
- Designed with insulated materials which prevent condensation
- Water drainage at the bottom of the ice bin
- CTM-SB
- Dimension: 760W x 800D x 1035mmH
- Capacity: 120kg / 268lb
- CTF-SB
  - Dimension: 535W x 800D x 1035mmH
  - Capacity: 80kg / 179lb









MANAGEMENT OFFICE & SHOWROOM |

1/F., NEW CITY CENTRE, 2 LEI YUE MUN ROAD,
KWUN TONG, KOWLOON, HONG KONG

TEL | 852-2723 2168 FAX | 852-2739 7576

WEBSITE | www.yot.com.hk



# CRYSTAL CCE

Crystal ICE

Ice Maker



# CRYSTAL ICE



### Ice Maker Series

RYSTAL ICE ice makers are the best choice when you have various preferences on ice.













# Design & Aesthetics for CRYSTAL ICE Ice Maker series



Imported compressor with — Constructed by AISI 304 Non-CFC refrigerant stainless steel (R134a / R404A) and ODP zero blowing agent

- Automatic ice production stopping and bin-full indicator
- Air-cooled type which reduces water consumption

# Accessories & Options

- Water filter
- Ice bin (Optional for CTM & CTF series)

Please refer to the last page for more information

	SL-50A	SL-100A	SL-200A
Dimensions (W x D x H) mm	457 x 522 x 728	457 x 522 x 910	675 x 521 x 1017
Voltage	230V / SPN	230V / SPN	230V / SPN
Loading (kW)	0.34	0.5	0.85
Refrigerant	Non-CFC R134a	Non-CFC R134a	Non-CFC R134a
Water Consumption (L/24hr)			
Maximum Production of Ice / 24hr (kg/lbs) (Temp. 10°C(Water) / 10°C(Environment))	23 / 51	38 / 84	86 / 189
Minimum Production of Ice / 24hr (kg/lbs) Temp. 32°C(Water) / 38°C(Environment))		26 / 57	58 / 128
Ice Bin Capacity (kg/lbs)			
Net Weight / Gross Weight (kg)	39 / 46	48 / 55	64 / 74

6

FULL DICE ICE CUBERS	CTM-453A		CTM series
Voltage	220-240V / SPN	220-240V / SPN	380-400V / TPN
Loading (kW)			
Refrigerant	Non-CFC R404a	Non-CFC R404a	Non-CFC R404a
Water Consumption (L/24hr)	336	468	624
Maximum Production of Ice / 24hr (kg/lbs) (Temp. 10°C(Water) / 10°C(Environment))	215 / 475	320 / 704	485 / 1067
Minimum Production of Ice / 24hr (kg/lbs) (Temp. 32*C(Water) / 38*C(Environment))	118 / 260	174 / 383	300 / 660
External Ice Bin (Standard Accessories)	CTM-SB	CTM-SB	CTM-SB
Net Weight / Gross Weight (kg)	70 / 85	73 / 88	104 / 122

ICE FLAKERS		CTF-1201A	CTF series
Voltage	230V / SPN	230V / SPN	
Refrigerant	Non-CFC R404a	Non-CFC R404a	
Maximum Production of Ice / 24hr (kg/lbs) (Temp. 10°C(Water) / 10°C(Environment))	320 / 705	600 / 1323	
Minimum Production of Ice / 24hr (kg/lbs) (Temp. 32°C(Water) / 38°C(Environment))	190 / 419	330 / 727	
	CTF-SB	CTF-SB	
Net Weight / Gross Weight (kg)	79 / 88	95 / 104	